

WG-604 HotSpot Gateway

The Powerful HotSpot Gateway/Router Solution for B&B, Coffee Shop/Restaurant, and Campus Library/Dormitory.



FEATURE

- Up to 200 concurrent users ever on a HotSpot gateway/router
- 3.5 times faster as bundling core processor with separate WLAN module
- 3 antennas to offer unparalleled performance
- Compatible with IEEE 802.11 b/g/n wireless LAN 2T3R
- RADIUS AAA support (RFC 2865/2866)
- Web-based authentication and management
- Support WPA/WPA2, 64/128 bit WEP data encryption, layer 2 isolation, and SSL login page to enhance security
- Support firewall functions: VPN (IPSec/PPTP/L2TP), PPTP VPN client, and IP/MAC/URL address pass through

AG-300E FEATURE

- Multi-function printer for account report printout
- IEEE 802.3af PoE (power over ethernet)
- One PS/2 port for connecting to a keypad
- 10/100Mbps transfer LED light
- Press combination hotkeys to generate billing and system summary
- Support additional 10 billing profiles with PS/2 keypad

DESCRIPTION

The WG-604 300Mbps HotSpot Gateway/Router provides unsurpassed wireless high speed for Bed & Breakfast, Coffee Shop/Restaurant, Airport/Transportation Center and Campus Library/Scenic Square to provide guests, visitors and customers a powerful WiFi hotspot network service. The product design is bundling core processor with separate WLAN module that allows users to enjoy 3.5 time faster than competitors' WLAN on Board. It is equipped with 3 antennas to offer the most concurrent users an unparalleled performance ever on a hotspot gateway.

The WG-604 provides a customizable and user-friendly management interface that supports web-based authentication and management tool, and marketing cooperation. It also can be integrated with RADIUS AAA server, pre-paid card system, billing system, SMTP server, web server, SNMP management and syslog server. It can work with AG-300E Account Generator Thermal Printer that allows the proprietors to generate a billing and system summary with a single kit simply.

AG-300E Account Generator


The Patented Hotspot Account Generator with a Single Click



DESCRIPTION

The AG-300E patented Account Generator Thermal Printer provides a simple hotkey to generate an account and print it out. It is designed to work with WG-604 HotSpot Gateway or ISS-7000 Internet Subscriber Server that offers Internet and billing service at the coffee shop, restaurant, office, lobby and meeting room. The AG-300E is a multi-function printer and generates billing and system summary by press combination hotkeys that includes daily account, monthly account, system status, and network report printout.

APPLICATION



WG-604 SPECIFICATION

Network specification	IEEE802.3 10Base TX Ethernet IEEE802.3u 100Base TX fast Ethernet IEEE802.11n Wireless LAN 300Mbps IEEE802.11g Wireless LAN 54Mbps IEEE802.11b Wireless LAN 11Mbps ANSI/IEEE 802.3 NWay auto-negotiation
Compatibility	All WiFi certificated wireless adapters Support all operation systems
Interface	4 LAN Ports (10Base T/ 100Base TX auto cross-over) 1 WAN Port (10Base T/ 100Base TX auto cross-over)
Wireless operation range	Up to 400 feet (outdoor)
Wireless data rate	Up to 300Mbps with auto fall back with 802.11b/g
Frequency band	2.4 GHz frequency band
Encryption	WPA/WPA2, 64/128 bit WEP data encryption
Power requirement	External power adaptor Input: 100-240 VAC, 50/60 Hz Output: 12V, 1.5Amp
Dimension	(L): 222mm / (W): 143mm / (H): 36mm Weight: about 500g (net)
Environmental conditions	Operating Temperature: 0°C to 50°C Storage Temperature: -10°C to 60°C Humidity: 10% ~ 90% non-condensing 10% ~ 80% condensing
Mounting	Desktop/ Wall mounted
Ip plug and play	Zero end-user configurations
Concurrent users	200

Authentication	Web-based authentication RADIUS AAA support (RFC 2865/2866) User authentication and accounting
Security and firewall	SSL User login page Layer 2 isolation security IP/MAC/URL address pass through VPN (IPSec/PPTP) pass through PPTP VPN client IP/URL filtering
Management	Configuration page Web-based management tool TFTP/HTTP firmware upgrade Wizard setup for step-by-step configuration Backup/Restore configuration file Remote authorized management Real-time session list LAN device management Syslog (System/ User/ Accounting and billing / LAN devices management) E-mail logs SNMP v1/v2 (MIB II)
Marketing cooperation	Standard login page Customizable log-on and log-off pages Advertisement URL link Walled garden WISPr smart client Logout window timer control
Certification	FCC/ CE/ C-Tick/ VCCI/ PCT

AG-300E SPECIFICATION

Interface	Ethernet
Printer tray	Push button: push to open printer cover Tear bar: cuts receipt paper Button A: flashing when printer cover is opened Paper roll housing: put paper roll here
Paper roll specification	Width: 58 (+1/-1) mm Length: 50 meters (max) Thickness: 65um Outside diameter: 63 (+2/-2) mm Inside diameter: 12 (+0.5/-0.5) mm Weight: 120 grams
Dimension	(L): 109 mm / (W): 155 mm / (H): 90 mm Weight: about 340g (net)

Input/output	DC power in Reset button PS2 keypad line out (optional) 10Mbps transfer LED light: green light will flash if 10Mbps throughput is transferred 100Mbps LED light: yellow light will flash if 100Mbps throughput is transferred
Environmental conditions	Operating temperature: 0 °C to 50°C Storage temperature: -10 °C to 60°C Humidity: 10% ~ 90% non-condensing 10% ~ 80% condensing
Certification	FCC/ CE/ C-Tick/ VCCI/ CSA



HANDLINK

Handlink Technologies, Inc.

4F, No. 3, Prosperity Rd. 1, Scienced-Based Industrial Park, Hsinchu 300, Taiwan, R.O.C.

Tel: +886-3-564-5166 Fax: +886-3-564-3922

E-mail: handlinksales@handlink.com.tw

http://www.handlink.com

Copyright © 2006-2015 Handlink Technologies Inc. all Rights Reserved.

